

PETRONAS TUTELA TRANSMISSION ATF XP-4

Premium Performance Synthetic Low-viscosity Multi-Vehicle Automatic Transmission Fluid (ATF)

PETRONAS Tutela Transmission ATF- XP4 is a technologically advanced and premium quality multi-vehicle automatic transmission fluid (ATF) specially formulated for 6-speed transmissions used in passenger cars and trucks that requires a low viscosity. It is engineered to meet Mitsubishi/Hyundai SP-IV, Toyota WS, Nissan Matic S specifications and suitable for service fill of most automatic transmissions manufactured by major Asian, American and European OEMs that specifies a lower viscosity ATF.

Formulated with premium quality synthetic base fluids and high performance additives technology to provide superior performance in oxidation stability, low-temperature flow, friction control, load-carrying ability, corrosion and wear protection, viscosity consistency and resistance to thermal breakdown. It protects the critical lubrication regimes in automatic transmissions especially against the formation of sludge, varnish, foams and other harmful deposits.

Applications

- Recommended for use in all automatic transmissions that requires low viscosity ATF and meets the specifications of Toyota WS, Nissan Matic S, Mitsubishi/Hyundai SP-IV.
- Not recommended to be used for CVT transmissions

Customer Benefits

- Provides outstanding fuel efficiency with its low viscosity features
- Excellent anti-shudder performance and enhanced friction durability for smooth and jerk-free operations
- Exceptional oxidation stability and effectively maintain stable viscosity over wider range of service applications
- Superior low temperature fluidity for excellent cold weather shifting performance
- Superior protection against wear, corrosion, and the formation of lacquers, sludge, or other harmful deposits

Product Typicals

Characteristics	Value
Density @ 15 °C, kg/l	0.844
Pour Point, °C	-48
Flash Point, °C	216
Kinematic Viscosity, cSt	
@ 40 °C	26.54
@ 100 °C	5.65
Brookfield Viscosity, cP	
@ - 40 °C	9,200
Viscosity Index	160
Colour	Red

Specifications

Suitable For Use:

- Mitsubishi/Hyundai SP-IV
- Toyota Type WS
- Nissan Matic S

Customer Advice

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.